

T-Slot Nuts (continued)

NEW Inch Sizes

Part No.	Tapped Through Part No.	Thread A	*English Table Slot B	**Metric Table Slot	C	D	E	F	Wt. (lbs/100 pcs)
41470	41470T	1/4-20	3/8	10MM	3/8	1/4	5/8	7/8	
41471	41471T	5/16-18	7/16	12MM	1/2	7/32	3/4	1	
41472	41472T	3/8-16	7/16	12MM	1/2	7/32	3/4	1	
41473	41473T	3/8-16	1/2	13MM	1/2	9/32	7/8	1	
41474	41474T	3/8-16	9/16	15MM	5/8	11/32	7/8	1	
41476	41476T	3/8-16	5/8	16MM	5/8	3/8	1	1	
41478	41478T	3/8-16	5/8	16MM	7/8	7/16	1-3/16	1-3/16	
41475	41475T	1/2-13	9/16	15MM	5/8	11/32	7/8	1	
41477	41477T	1/2-13	5/8	16MM	5/8	3/8	1	1	
41479	41479T	1/2-13	5/8	16MM	7/8	7/16	1-3/16	1-3/16	
41480	41480T	1/2-13	11/16	18MM	3/4	13/32	1-1/8	1-1/8	
41481	41481T	5/8-11	11/16	18MM	3/4	13/32	1-1/8	1-1/8	
41482	41482T	5/8-11	3/4	20MM	3/4	1/2	1-1/4	1-1/8	
41483	41483T	5/8-11	13/16	21MM	1	9/16	1-3/8	1-1/2	
41484	41484T	3/4-10	13/16	21MM	1	9/16	1-3/8	1-1/2	
41486	41486T	3/4-10	13/16	21MM	1	17/32	1-1/4	1-1/2	
41485	41485T	3/4-10	7/8	23MM	1	5/8	1-1/2	1-1/2	
41487	41487T	3/4-10	1	26MM	1-1/4	3/4	1-1/2	1-1/2	
41488	41488T	7/8-9	1	26MM	1-1/2	3/4	1-3/4	1-1/2	
41490	41490T	7/8-9	1-1/16	27MM	1-1/2	3/4	1-3/4	1-1/2	
41489	41489T	7/8-9	1-1/8	29MM	1-1/2	3/4	1-3/4	1-1/2	
41491	41491T	1-8	1-1/8	29MM	1-1/2	3/4	1-3/4	1-3/4	

Metric

Part No.	Tapped Through Part No.	Thread A	**Metric Table Slot	*English Table Slot B	C	D	E	F	Wt. (lbs/100pcs)
61401	61401T	M6 x 1.0	8MM	5/16	10	6	14	19	3
61402	61402T	M6 x 1.0	10MM	7/16	11	6	16	22	5
61403	61403T	M8 x 1.25	10MM	7/16	11	6	16	22	5
61404	61404T	M10 x 1.5	12MM	1/2	13	7	19	22	6
61405	61405T	M10 x 1.5	14MM	9/16	16	9	22	29	12
61406	61406T	M12 x 1.75	14MM	9/16	16	9	22	29	12
61407	61407T	M12 x 1.75	16MM	5/8	16	9	25	29	14
61408	61408T	M12 x 1.75	17MM	11/16	19	11	29	32	21
61409	61409T	M16 x 2.0	18MM	3/4	19	11	29	32	19
61410	61410T	M16 x 2.0	20MM	13/16	25	14	32	38	36
61411	61411T	M20 x 2.5	22MM	7/8	25	14	35	38	36
61412	61412T	M24 x 3.0	27MM	1-1/16	29	18	41	51	69
61413	61413T	M24 x 3.0	33MM	1-5/16	32	24	51	51	106

Stainless Steel T-Nuts

- 300 Stainless Steel
- The last thread is incomplete to prevent the stud from turning through the bottom of the nut.



* T-Nuts are undersized to fit machine table slot.

Part No.	Thread A	*English Table Slot B	C	D	E	F	Weight (lbs/100pcs)
47401	1/4-20	5/16	1/4	3/16	1/2	9/16	3
47403	5/16-18	3/8	3/8	1/4	5/8	7/8	6
47404	3/8-16	7/16	3/8	13/64	5/8	7/8	6.5
47405	3/8-16	1/2	1/2	9/32	7/8	7/8	9
47409	1/2-13	9/16	1/2	11/32	7/8	1-1/8	12
47410	1/2-13	5/8	5/8	11/32	1	1-1/8	15
47412	1/2-13	11/16	3/4	7/16	1	1-1/4	22
47415	5/8-11	11/16	3/4	7/16	1	1-1/4	20
47416	5/8-11	3/4	3/4	15/32	1-1/4	1-1/4	23